



ONVIF 3 Megapixel Vandal Dome

IP Camera




NEW 2012 OCT. V2.1



IP Surveillance VIT-DA651

- High quality 1/2.5" CMOS Sensor
- Real-time H.264, MPEG-4 and MJPEG Compression (Triple Codec)
- Simultaneous Multiple Streams
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- Built-in SD/SDHC Card Slot for On-board Storage
- Supports H/W Watchdog
- Vandal-Resistant Case Design

VIT-DA651 3 Megapixel Vandal Dome IP Camera




OPTIONAL

SPECIFICATIONS

System	CPU : TI DM365 SoC	
	Flash : 32MB	
	RAM : 128MB	
Image Sensor	High Quality 1/2.5"CMOS	
Lens	Varifocal 3.5-10mm F1.6	
	Removable IR-cut filter for day & night function	
Sensitivity	0 Lux(IR ON)	
IR LED	30PCS LEDs	
Video	H.264: 30 fps at 1280x720 , Highest Resolution: 15 fps at 2048x1536	
	MPEG4: 30 fps at 1280x720 , Highest Resolution: 23 fps at 1920x1080	
	MJPEG: 30 fps at 1280x720 , Highest Resolution: 15 fps at 2048x1536	
	Compression: H.264, MPEG-4 & MJPEG Streaming: Triple Codec	
	(H.264 、 MPEG-4 、 JPEG) Selectable	
	Support Simultaneous multiple streams	
Image Settings	Adjustable image size, quality, and bit rate	
	Time/Date stamp and text caption overlay.	
	Configurable brightness, contrast, saturation, sharpness, white balance and exposure AGC / AWB / AES / BLC	
Audio	Format	MPEG-4 AAC audio encoding
		G.711 audio encoding
	Support Audio line-in for external microphone	
Networking	Interface	10/100 Mbps Ethernet, RJ-45
	Supported Protocol	IPv4,TCP/IP,DHCP,HTTP,RTSP,SNTP,DNS
	Supported Browser	Microsoft Internet Explorer 6.0 or above. QuickTime Player is necessary add-in for Safari, Chrome or Firefox
Alarm and Event Management	Motion Detection	
	Event notification using SMTP or FTP through CMS FCW-SE064	
	Smart Motion Detection Triggered Nighttime color image	
Users	8 clients on-line monitoring at the same time	
	Multi-level user access control with password protection	
On-board Storage	Micro SD/SDHC card slot : Stores snapshots and video clips	
Maintenance	Supports online firmware upgrade	
I/O	RJ-45 Ethernet, DC Jack, BNC Video out, Phone Jack Line in, MicroSD Slot	
Power	DC12V or PoE IEEE802.3af Class 0(Optional)	
Weight	Netweight : 1050g	
Dimension	W:Φ150mm H:110mm	
Operating Environments	Temperature: 0 ~ 45 °C ; Humidity: 90%	

★Version updating is not going to inform, please check the on-going updating information



■ DISTRIBUTED BY

