

ST-DX7104/7108/7116T-LM

Mini 1U 1 SATA 4/8/16ch Analog HD DVR



Features

- > Support ADH-M series front-end real-time encoding;
- > Support VGA, HDMI HD output;
- > Support P2P Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- > Support various mobile monitoring: (IOS, Windows Mobile, BlackBerry, Symbian, Android) .
- > Support multiple web browsers (IE,Chrome,Firefox,Safari) ;
- > Support more than 20 languages (English,Finnish, French, German, Greek, Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, Chinese, Traditional Chinese, Turkish, etc.) , no nation boundaries;
- > perfect protection circuit, unique triple watchdog function
- > Supporting web, CMS, center platform management software, provide SDK development.

Saitell Technology Co., Ltd.

China Shenzhen Foreign Trade (Group) Building, 239 Zhongxing Road, Shenzhen, China
Tel: +86-755-22318209 Fax: +86-755-22318205 Email:sales@saitell.com www.saitell.com

ST-DX7104/7108/7116T-LM

Technical Specifications

	Model	ST-DX7104T-LM	ST-DX7108T-LM	ST-DX7116T-LM
System	Main processor	Huawei Hi 3520D	Huawei Hass 3521	Huawei Hass 3531
Video	video compression	H.264(High Profile);		
	Encode	4*AHD-M	8*720P@12fps	16*720P@12fps
	Decode	1*AHD-M	4*720P@12fps	4*720P@12fps
	Multi-mode input	Pure Analog: 4*AHD-L;4*AHD-M Mixed: 2*720P(analog) +2*720P(network); Pure Network: 8*720P; 1*1080P; 4 *720P; 8*1080P;4*1080P	Pure Analog: 8*720P; 4*720P; 8*AHD-L; Mixed: 4*720P(Analog) +4*720P(Network); Pure Network: 8*720P; 2*1080P+2*720P;	Pure Analog: 16*720P; 8*720P;16*AHD-L; Mixed: 4*720P (Analog) +4*720P(Network); Pure Network: 1*1080P+8*720P; 4*1080P; 20* 960H
Audio	Audio compression	G.711A		
	Intercom	support		
Recording and Playback	Record mode	Manual>alarm>motion detection>timing		
	Playback Channels	4 (pure local input mode)		
Storage and backup	Space occupation	960H: 12~20G/ day*channel720P: 20G/ day*channel audio: 691.2M/ day*channel		
	Backup mode	Network backup、USB HDD, USB writer、SATA writer		
Interface	Video input	4 BNC	8 BNC	16 BNC
	Video output			
	Audio input	4ch RCA	8ch RCA	2ch RCA
	Audio output	1ch RCA		
	Alarm input	N/A		
	Alarm output	N/A		
	Network interface	RJ45 10M/100M Adaptive Ethernet port		
	PTZ control	RS485; support multiple PTZ protocols		
	USB	2 USB ports		
	Hard disk	1 SATA (Each maximum support 4T)		
	Wireless	3G、WIFI(expand via USB)		
Other	Power	12V/2A		
	dimension	255mm(length)* 225mm(width)* 45mm(height)		

Saitell Technology Co., Ltd.

China Shenzhen Foreign Trade (Group) Building, 239 Zhongxing Road, Shenzhen, China
 Tel: +86-755-22318209 Fax: +86-755-22318205 Email:sales@saitell.com www.saitell.com