

## ST-IPCL1131/1200/1201/1301VDR20-V

---

1.3/2.1/2.4/3.2Mp IR Vandalproof & Waterproof Dome Network Camera



### Features

- > ST-IPCL1131VDR20-V: 1/3" SONY Low Illumination 1.3MP CMOS Sensor
- ST-IPCL1200VDR20-V: 1/2.7" OV 2.1MP High-resolution CMOS Sensor
- ST-IPCL1201VDR20-V: 1/2.9" SONY Low Illumination 2.4MP CMOS Sensor
- ST-IPCL1301VDR20-V: 1/2.8" SONY 3.2MP Starvis Back-illuminated CMOS Sensor
- > IR LEDs length 20m, 5x21pcs
- > Focal Length 2.8-12 mm
- > DC12V, IP66

---

### Saitell Technology Co., Ltd.

China Shenzhen Foreign Trade (Group) Building, 239 Zhongxing Road, Shenzhen, China  
Tel: +86-755-22318209 Fax: +86-755-22318205 Email: sales@saitell.com www.saitell.com

**ST-IPCL1131/1200/1201/1301VDR20-V**

**Specifications:**

Model	ST-IPCL1131VDR20-V	ST-IPCL1201VDR20-V	ST-IPCL1200VDR20-V	ST-IPCL1301VDR20-V
<b>Camera</b>				
Image Sensor	IMX225	IMX322	OV2710	IMX124
Main processor	HI3518C	HI3516C	GM8136S	S2L
Resolution	960P	1080P	1080P	1080P
Effective Pixels	1280(H)*960(V)	1920(H)*1080(V)	1920(H)*1080(V)	2048(H)*1536(V)
TV System	PAL/NTSC			
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec			
Sync System	Internal	Internal	Internal	External
Usable Illumination	0.01Lux	0.01Lux	0.01Lux	0.1Lux
S/N Ratio	≥52dB			
Scanning System	Progressive			
Video Output	Network			
<b>Lens</b>				
Focus Length	2.8-12mm			
Focus Control	Manual			
Lens Type	Manual			
<b>Night Vision</b>				
Infrared LED	∅ 5X21PCS			
Infrared Distance	20M			
IR Status	Under 10 Lux By CDS			
IR Power On	CDS Auto Control			
<b>Network</b>				
Ethernet	RJ-45 (10/100Base-T)			
Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS			
ONVIF	Support ONVIF 2.4			
P2P	YES, Support QR Code			
POE	Optional, Support IEEE 802.3af			
WIFI	N/A			
Video Delay	0.3S (Within the Lan)			
Main Stream	1280*960@30fps	1920*1080@30fps	1920*1080@30fps	1920*1080@30fps

**Saitell Technology Co., Ltd.**

China Shenzhen Foreign Trade (Group) Building, 239 Zhongxing Road, Shenzhen, China  
 Tel: +86-755-22318209 Fax: +86-755-22318205 Email:sales@saitell.com www.saitell.com

**ST-IPCL1131/1200/1201/1301VDR20-V**

Sub Stream	704*576@30fps, 352*288@30fps	704*576@30fps, 352*288@30fps	704*576@30fps, 352*288@30fps	704*576@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)			
Smart Phone	iPhone, iPad, Android, Android Pad			
<b>Camera Features</b>				
Day/Night	Color/ B&W (IR-CUT )			
Compression	H.264/JPEG,Support record AVI format.			
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)			
Motion Detection	Support			
Privacy Masking	3 Rectangular Zone			
WDR	YES			
Recording Mode	NVR/NAS/CMS/Web			
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian			
<b>General</b>				
Housing	Vandalproof (Metal, IP66)			
Anti-cut Bracket	Yes, 3-Axis Bracket Built-in for Lens Adjustment			
IR Cut Filter	YES			
Operation Temperature	-10°C ~ +50°C RH95% Max			
Storage Temperature	-20°C ~ +60°C RH95% Max			
Power Source	DC12V±10%, 500mA			
Dimension	φ148×111(H)mm			
Weight	1.2KG			

**Saitell Technology Co., Ltd.**

China Shenzhen Foreign Trade (Group) Building, 239 Zhongxing Road, Shenzhen, China  
 Tel: +86-755-22318209 Fax: +86-755-22318205 Email:sales@saitell.com www.saitell.com